

Product Benefit Sheet

Revised: 2016/11/25 (version 1.0)



PETRONAS Sprinta F300 20W-40

Designed with UltraFlex™, that enhances oil stability to resist bike stress

Motorcycle riders rely heavily on their bikes for work or leisure. Stress to the motorcycles can easily built up within short period of time, even under normal riding conditions. This is due to motorcycle engines generally work harder than car engines and subject to tremendous stress! A good motorcycle oil is flexible in handling these diverging effects of bike stress.

Description and Applications

PETRONAS Sprinta F300 20W-40 is formulated with UltraFlex™ technology that enhance oil stability to resist bike stress. This helps to deliver better ride, giving your bike a longer life.

PETRONAS Sprinta F300 20W-40 is suitable for all types of 4-Stroke gasoline motorcycle engines, clutches and gear boxes. It is suitable for motorcycles manufactured by leading Japanese, European and American manufacturers operating under normal to severe riding conditions.

Note: Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle

Features and Benefits

Main Benefit(s):

- Superior control in deposit build ups especially under high operating temperature, helps maintaining bike power.

Also delivers:

- Helps preventing clutch slippage, delivering superior drivability.
- Provides superior engine, gear & clutch protection, helps to prolong component life.

Specifications and Approvals

PETRONAS Sprinta F300 20W-40 is a premium lubricants that meets and exceeds below performances:-

Meets or Exceeds the requirements of:	
API SM	√
JASO MA2	√

* All technical data is provided for reference only.

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: www.pli-petronas.com

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.

Code: 3003