

# Product Benefit Sheet

Revised: 2017/03/07 (version 1.1)



## PETRONAS Urania 800 25W-60

### Designed for Superior Protection for High Mileage Diesel Vehicles

#### Description and Applications

PETRONAS Urania 800 25W-60 is formulated with advanced lubricant technology that provides superior sealant effect that combats leaks and oil consumption, which is critical for high mileage/ older diesel vehicles.

PETRONAS Urania 800 25W-60 is suitable for most types of high mileage heavy duty diesel applications including modern and high-output engines. It is also suitable for new and old turbocharged and naturally aspirated diesel engines, both on-highway and off-highway, running on high or ultra-low Sulphur diesel and bio-diesel.

Note: Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle

#### Features and Benefits

Delivers:

- Superior sealant effect that reduces oil leaks, delivering protection to worm engine parts for older vehicles and also power recovery.
- Superior control in deposit build ups (soot & sludge), delivering superior protection.
- Its alkaline reserve (TBN) enables effective combats against acidic levels leads to corrosion, making your fleet engines more durable.

#### Specifications and Approvals

PETRONAS Urania 800 25W-60 is a lubricants that meets and exceeds below performances:-

Meets or Exceeds the requirements of:

API CG-4	√
----------	---

\* All technical data is provided for reference only.

#### Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refers to product SDS or contact us at: [www.pli-petronas.com](http://www.pli-petronas.com)

### **Important Note**

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contains herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortuous action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.

Code: 2186