

PETRONAS HYDRAULIC PLUS SERIES

Premium Performance Anti-wear Hydraulic Fluids

PETRONAS Hydraulic Plus Series are premium performance anti-wear hydraulic fluids specially developed for a wide range of modern mobile and industrial hydraulic equipment operating under normal to extremely heavy duty conditions including latest high speed and high pressure systems. Formulated with the highest quality selected base oils enhanced with advanced anti-wear, anti-oxidant, anti-rust and anti-foam additives coupled with friction modifiers, PETRONAS Hydraulic Plus fluids provide excellent anti-wear protection under toughest operating conditions and up to 5x longer lasting performance*.

PETRONAS Hydraulic Plus Series meet or exceed key industrial specifications and OEM requirements including latest Bosch Rexroth RDE 90235 specification.

*vs. minimum requirements of ISO 11158 HM for anti-wear hydraulic fluids based on TOST (ASTM D943)

Applications

PETRONAS Hydraulic Plus Series are recommended for use in:

- various mobile and industrial hydraulic systems operating under normal to extremely heavy duty conditions
- modern hydraulic systems using high speed & high pressure pumps and operating under high temperatures
- hydraulic systems with smaller reservoirs & smaller coolers generating high thermal stress on hydraulic fluids
- sensitive to sludge and varnish formation systems with tight tolerance pumps and servo valves
- hydraulic systems demanding long life lubricants

Features and Benefits

Features	Benefits
Low temperature protection	Ensures proper protection of equipment components during cold starts
Excellent anti-wear protection	Protects equipment components from excessive wear and provides longer equipment life
Excellent wet and dry filterability	Maintains excellent filter efficiency without giving rise to undue pressure drop, thus increasing filter lifetime.
Excellent thermal and oxidation stability	Maintains performance levels under high temperatures and pressure, enabling long oil drain intervals
Excellent rust & corrosion protection	Inhibits the corrosion process that occurs in presence of water, improving equipment life



PETRONAS

Technical Data Sheet
Version 2.0_13.04.2017

PETRONAS HYDRAULIC PLUS SERIES

Premium Performance Anti-wear Hydraulic Fluids

Features	Benefits
Excellent water separability	Due to excellent water separability the system is protected from water degenerative effects, maintaining hydraulic system efficiency at required level and reducing maintenance costs
Excellent air release and foam stability	Maintains excellent efficiency in hydraulic systems, ensures smooth operation due to fast air release. Protects the system from air degenerative effects reducing maintenance costs
Excellent multi metal compatibility	Compatible with most metal alloys ensuring trouble free performance of the system
Excellent compatibility with most seal and elastomers	Compatible with most seals and elastomers, which prevents oil leaks and contamination due to seal erosion

Typical Properties

Characteristic	Method	Specification	32	46	68
Specific Gravity @15°C	ASTM D 4052	(1)	0,871	0,867	0,868
Kinematic Viscosity at 40°C, cSt	ASTM D 445	±10%	32	46	68
Kinematic Viscosity at 100°C, cSt	ASTM D 445	**	5,4	6,9	8,8
Viscosity Index	ASTM D 2270	(1)	102	105	102
Flash Point, °C	ASTM D 92	Report	220	220	230
Pour Point, °C	ASTM D 97	**	-33	-33	-30
TAN, mgKOH/g	ASTM D 664	(1)	0,40	0,40	0,40
FZG, Stages Passed	ISO 14635-1	Min. 10	10	10	10
Water Separability, 40/37/3 - mins	ASTM D 1401	**	10	10	15
Copper Strip Corrosion	ASTM D 130	Max. 2	1a	1a	1a
TOST life, hours	ASTM D 943	Min. 1000	5200	5200	5200
Foam Sequence I, mL		Max. 150/0	0/0	0/0	0/0
Foam Sequence II, mL	ASTM D 892	Max. 75/0	0/0	0/0	0/0
Foam Sequence III, mL		Max. 150/0	0/0	0/0	0/0

All technical data is provided for reference only and all specification based on DIN 51524-2 (2006) and ISO 11158 HM (FDIS 2008)

**Individual limits accordingly with each viscosity grade / (1): not required in specification / SS is available upon request including quality control limits

www.pu-petronas.com

ALL RIGHTS RESERVED. THIS PRODUCT DATA SHEET (INCLUDING NAME, INFORMATION, LOGOS, IMAGES, PICTURES AND ICONS) WHICH RELATES OR REFERS TO PETRONAS LUBRICANTS INTERNATIONAL (PLI) IS THE SOLE AND ABSOLUTE PROPERTY OF PLI AND/OR ITS HOLDING COMPANY AND SHALL BE TREATED AS PRIVATE AND CONFIDENTIAL. NO PART OF THIS DOCUMENT MAY BE REPRODUCED, STORED IN A RETRIEVAL SYSTEM OR TRANSMITTED IN ANY FORM OR ANY MEANS (ELECTRONIC, MECHANICAL, RECORDING OR OTHERWISE) WITHOUT THE PERMISSION OF PLI AND/OR ITS HOLDING COMPANY.

PETRONAS HYDRAULIC PLUS SERIES

Premium Performance Anti-wear Hydraulic Fluids

Performance Levels

- Bosch Rexroth RDE 90235 (Listed on the Fluid Rating List RDE 90245)
- DIN 51524 Part II HLP (2006)
- Eaton 03-401-2010
- Eaton Lubricant Specification E-FDGN-TB002-E
- Fives Cincinnati P-68/P-69/P-70
- ISO 11158 HM (FDIS 2008)
- Parker Denison HF0/HF1/HF2

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: www.pli-petronas.com

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortuous action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.