

PETRONAS GREASE FG

Aluminium Complex Food Grade Grease

PETRONAS Grease FG is an Aluminium complex grease specially developed for lubrication of machinery used in food processing and packaging industries.

Formulated with white base oils enhanced with Aluminium complex soap, extreme pressure, anti-oxidant, anti-rust, corrosion inhibitor and anti-bacterial additives. PETRONAS Grease FG provides excellent high temperature performance, high load carrying capabilities and excellent adhesiveness qualities which makes it ideal for components where there is oscillating or rotating motion.

PETRONAS Grease FG meets NSF H1 (Former USDA 1998 H1 type) guidelines for greases used in applications where incidental food contact may occur and is manufactured using white oils and other ingredients which are permitted substances for the preparation of lubricants in terms of the FDA regulation 21 CFR 178.3570.

Applications

PETRONAS Grease FG is recommended for use in:

- lubrication of equipment in the food processing industries with a wide range of operating conditions in applications that include all enclosed Journal and anti-friction bearings, slides and cams
- in plant and mobile equipment handling food products where food contact will occur.
- typical applications include, bottlers, canners, seaming rolls, slicers, peelers, cutters, dicers, hydrostatic cookers, grain handling equipment, malting operations and packaging equipment.

Note: PETRONAS Grease FG is recommended for operating temperature range of -20°C to +150°C.

PETRONAS GREASE FG

Aluminium Complex Food Grade Grease

Features and Benefits

Features	Benefits
Food grade approval	Designed specifically for the lubrication of food processing machinery under a wide range of operating conditions
Excellent pumpability	Excellent performance where low temperature performance is required
Excellent load carrying capacity	Contains special additives which enables the grease to withstand heavy loads without losing the lubricant film
Excellent rust & corrosion protection	Protects bearing surfaces against rust and corrosion, even when the grease is contaminated with water
Excellent resistance to water wash-out and water spray off	Equipment protection and good lubrication even in presence of water
High thermal and oxidation stability	Has good oxidation resistance and can withstand high operating temperatures without hardening or forming bearing deposits
Excellent oil bleed control	Has an excellent controlled oil bleed and does not separate under storage

PETRONAS GREASE FG

Aluminium Complex Food Grade Grease

Typical Properties

Characteristic	Method	Specification	FG
Thickener Type	-	Aluminium Complex	Aluminium Complex
NLGI	ASTM D217	2	2
Color	Visual	White	White
Worked Penetration, mm/10	ASTM D217	265 - 295	282
Oil Separation, Mass %, Max.	ASTM D1742	3	2
Dropping Point, °C, Min.	ASTM D2265	230	240
Four Ball Wear, mm, Max.	ASTM D2266	0.70	0.70
Four Ball EP Weld Point, Min.	ASTM D2596	500	500
Roll Stability, % of Penetration Change, Max.	ASTM D1831	10	5
Wheel Bearing Leakage, grams, Max.	ASTM D4290	8	5
Water Washout, %, Max.	ASTM D1264	8	3
Water Spray off, %, Max.	ASTM D4049	30	20
Rust Protection, rating	ASTM D1743	Pass	Pass
Base Oil Viscosity @40°C, cSt	ASTM D445	450 - 470	460

All technical data is provided for reference only / SS is available upon request including quality control limits

Performance Levels

- DIN 51502 KP2K-20
- Halal Certified*
- ISO 12924 XBCDB2
- Kosher Certified*
- NSF H1 Registered*

*under certification

PETRONAS GREASE FG

Aluminium Complex Food Grade Grease

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: www.pli-petronas.com

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.