

PETRONAS GREASE LiCa MG HL

Extreme Pressure Lithium Calcium Grease

PETRONAS Grease LiCa MG HL is an extreme pressure Lithium Calcium grease with dual solid additives and film thickening polymers to improve boundary lubrication. Formulated with selected mineral base oils enhanced with Lithium calcium soap, advanced extreme pressure, anti-oxidant, anti-rust and corrosion inhibitor additives. PETRONAS Grease LiCa MG HL provides excellent load carrying protection, water washout and spray off resistance in applications operating in wet environments and elevated temperatures.

PETRONAS Grease LiCa MG HL meets or exceeds key industrial specifications.

Applications

PETRONAS Grease LiCa MG HL is recommended for use in:

- chassis grease and it is particularly suitable for off-road applications in civil engineering pin and bush lubrication, the agriculture sector and construction vehicles plus equipment
- slow speed heavy duty industrial plain and anti-friction bearings
- applications involving oscillating or limited relative motion, where fretting is likely to occur
- constant velocity joints, machine tools, vibrating shafts and sliding mechanisms

Note: PETRONAS Grease LiCa MG HL is recommended for operating temperature range of -20°C to +130°C.

Features and Benefits

Features	Benefits
Excellent pumpability	Excellent performance where low temperature performance is required
Excellent load carrying capacity	Contain special EP additives which enable the grease to withstand heavy shock loads without losing the lubricant film
High rust & corrosion protection	Protect bearing surfaces against corrosion, even when the grease is contaminated with water
High resistance to water wash-out	Equipment protection and good lubrication even in presence of water
High friction reduction capabilities	Dual solid lubricants reduce friction and assists energy savings

PETRONAS GREASE LiCa MG HL

Extreme Pressure Lithium Calcium Grease

Typical Properties

Characteristic	Method	Specification	LiCa MG HL
Thickener Type	-	Lithium Calcium	Lithium Calcium
NLGI	ASTM D217	2	2
Color	Visual	Dark Grey	Dark Grey
Worked Penetration, mm/10	ASTM D217	265 - 295	280
Worked Penetration 100.000x, Penetration Change, mm/10, Max.	ASTM D217	+30	+25
Oil Separation, Mass %, Max.	ASTM D1742	6	5
Dropping Point, °C, Min.	ASTM D2265	180	190
Four Ball Wear, mm, Max.	ASTM D2266	0.50	0.40
Four Ball EP Weld Point, Min.	ASTM D2596	400	400
Roll Stability, % of Penetration Change, Max.	ASTM D1831	10	10
Water Washout, %, Max.	ASTM D1264	5	3
Rust Protection, rating	ASTM D1743	Pass	Pass
Base Oil Viscosity @40°C, cSt	ASTM D445	660 - 680	670
Molybdenum Disulfide, Mass %	-	2	2
Graphite, Mass %	-	3	3

All technical data is provided for reference only / SS is available upon request including quality control limits

Performance Levels

- DIN 51502 KPF2K-20
- ISO 12924 XBCHB2

PETRONAS GREASE LiCa MG HL

Extreme Pressure Lithium Calcium Grease

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: www.pli-petronas.com

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.