

PETRONAS GEAR SYN SERIES

Premium Performance Synthetic Industrial Gear Oil

PETRONAS Gear Syn Series are premium performance industrial gear oils specially developed for wind turbines and various types of enclosed industrial gears operating under normal to extremely heavy duty conditions.

Formulated with high viscosity index synthetic base oil enhanced with advanced extreme pressure, anti-oxidant, anti-rust and anti-foam additives, PETRONAS Gear Syn oils provide clean-gear performance, excellent extreme pressure and Micro-pitting protection, anti-wear, superior performance across wide temperature range, and provides energy saving opportunities with reduced bulk oil temperatures, smooth operation of the gear drives and up to 2x longer lasting performance*.

PETRONAS Gear Syn Series meets or exceeds key industrial specifications and OEM requirements.

*vs. minimum requirements of industrial gear oils to pass the viscosity increase test (ISO 4263-4 @95°C)

Applications

PETRONAS Gear Syn Series are recommended for use in:

- wind turbine gear drives
- mining – gear drives requiring additional protection such as conveyer belts, shaft winder gear drives, mills, crushers, separators and other processing units
- steel and cement heavy duty industrial gear drives
- power generation gear drives such as mills and heavily loaded gear drives

PETRONAS Gear Syn is compatible with mineral oil or PAO based products

Features and Benefits

Features	Benefits
Excellent micropitting resistance	Helps to extend gear and bearing life in gear drives operating under severely loaded conditions
Low temperature protection	Ensures proper protection of equipment components in areas operating at low temperatures
High viscosity index	Ensures supreme performance and protection over a wide temperature range
Excellent extreme pressure protection	Excellent extreme pressure performance giving long gear life in severely loaded gear drives
Excellent anti-wear protection	Protects equipment components from excessive wear and provides longer equipment life
Excellent thermal and oxidation stability	Maintains performance levels under high temperatures and pressure, enabling long oil drain intervals
Excellent resistance to sludging	Excellent cleanliness for sludge free gear drives

www.pu-petronas.com

PETRONAS GEAR SYN SERIES

Premium Performance Synthetic Industrial Gear Oil

Features	Benefits
Very good rust & corrosion protection	Inhibits the corrosion process that occurs in presence of water, improving equipment life
Very good seal & paint compatibility	Compatible with most seals & paints in modern gear drives, which ensures gear drive cleanliness
Very good multi metal compatibility	Compatible with most metal alloys ensuring trouble free performance of the system

Typical Properties

Characteristic	Method	Specification	150	220	320	460	680
Specific Gravity @15°C	ASTM D 4052	Report	0,880	0,882	0,891	0,900	0,907
Kinematic Viscosity at 40°C, cSt	ASTM D 445	±10%	150	220	320	460	680
Kinematic Viscosity at 100°C, cSt	ASTM D 445	(1)	20,5	27,5	37,2	48,3	64,7
Viscosity Index, min	ASTM D 2270	**	159	161	165	165	167
Flash Point, °C	ASTM D 92	Min. 200	218	218	218	218	218
Pour Point, max °C	ASTM D 97	**	-39	-39	-39	-36	-33
Water Separability, 42/38/0 - mins	ASTM D 1401	**	15	15	30	35	5
Copper Strip Corrosion, Visual	ASTM D130	Max. 1	1a	1a	1a	1a	1a
Foam Sequence I, mL	ISO 6427	Max. 100/10	30/0	30/0	0/0	0/0	0/0
Foam Sequence II, mL		Max. 100/10	10/0	10/0	20/0	40/0	30/0
Foam Sequence III, mL		Max. 100/10	0/0	0/0	0/0	0/0	0/0
Weld Load, Kgf	ASTM D2783	(1)	250	250	315	250	250
FZG, Stages Passed	ISO 14635-1	Min. 12	>12	>12	>12	>12	>12

All technical data is provided for reference only and all specification based on DIN 51517-3 and ISO 12925-1

**Individual limits accordingly with each viscosity grade / (1): not required in specification / SS is available upon request including quality control limits

Performance Levels

- David Brown Type G lubricant
- DIN 51517 Part III
- HANSEN (HP1, HP2, HPP, P4 and M4ACC)
- SIEMENS MD (Revision 15) Table T 7300 A – g

PETRONAS GEAR SYN SERIES

Premium Performance Synthetic Industrial Gear Oil

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: www.pli-petronas.com

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.