

Product Data Sheet

Revised: 2019/07/23 (version 1.0)



PETRONAS

PETRONAS Sprinta F700 15W-50

Engineered with UltraFlex™, for instant defence and responsive performance

Motorcycle riders rely heavily on their bikes for work or leisure, they simply want to go ahead. Rides can be challenging with unexpected twists, turns, obstacles and opportunities: that is for commuter bikers who sense the overload with their hand on the throttle and it's true for the leisure riders seeking the freedom to ride how they want. The motorcycle oil needs to react instantly to the rapidly-changing road and riding conditions - reaching all the bike's critical parts fast and enabling them to perform from cold to start, in the traffic and out on the open road

Description and Applications

PETRONAS Sprinta F700 15W-50 is formulated with UltraFlex™ technology is engineered to react instantly to the different demands of all your bike's critical areas delivering instant defense and responsive performance.

PETRONAS Sprinta F700 15W-50 is a semi-Synthetic engine oil suitable for all types of 4-Stroke motorcycle engines, clutches and gear boxes especially for last generation motorcycles requiring JASO MA2 or MA, API SM lubricants. It is suitable for motorcycles manufactured by leading Japanese, European and American manufacturers.

Semi-Synthetic engine oil suitable for all types of 4-Stroke motorcycle engines, clutches and gear boxes especially for last generation motorcycles.

Note: Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle

Benefits

PETRONAS Sprinta F700 15W-50, formulated with the UltraFlex™ Technology flexes and defends critical parts instantly delivering a responsive performance through:

- Excellent oil film and shear strength, high viscosity stability to enhance engine performance and keeping optimal fuel economy
- Provides excellent engine, gear & clutch protection exceeding specification requirements and extending the bike's life
- Prevents clutch slippage and enhances clutch performance for high bike responsiveness

In addition, PETRONAS Sprinta F700 15W-50

- Provides excellent oxidation resistance and low volatility, providing extended drain intervals
- Meets the requirements of bikes fitted with catalytic converters with low sulfur and phosphorus formulation
- Meets the latest environmental compliance standards

Approvals, Specifications and Recommendations

PETRONAS Sprinta F700 15W-50 is a synthetic technology lubricant that meets and exceeds below performance:

Approvals and Specifications:

- API SM
- JASO MA2

Note: Always consult your owner's manual to check recommended viscosity grade and specifications for your specific vehicle

Typical Physical Data

Parameters	Method	Unit	Typical Value
Appearance	-	-	Bright & Clear
Density @15°C	ASTM D 4052	g/cm ³	0.857
Kinematic Viscosity @100°C	ASTM D 445	mm ² /s (cSt)	14.5
Viscosity Index	ASTM D 2270	-	161
Flash Point COC	ASTM D 92	°C	250
Sulphated Ash	ASTM D 874	%	0.9
TBN	ASTM D 2896	mgKOH/g	10.1
Pour Point	ASTM D97	°C	-33
Foam at 24°C	ASTM D 892	ml	0

All technical data is provided for reference only. These characteristics are typical of current production. Whilst future production will conform to PLI's specification, variations in these characteristics may occur.

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: www.pli-petronas.com

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.

Code: 73127